



Long-Rail Transport Unit STS

Technical Datasheet

STS 1001–STS 1008 / STS 2001–STS 2004 /

STS 3001–STS 3025 / STS 5001–STS 5007

STS Long-Rail Transport Unit: our freight wagons with special superstructure

Vossloh has equipped standard freight cars for the transport of long-rails with with special attachments. These long-rail transport units have cross members that make loading timbers and fastenings unnecessary.



Benefits

- / Extremely versatile deployment
- / Rails from 15 m up to 180 m in length can be loaded and unloaded
- / Special superstructure shortens loading times
- / Can be combined with Vossloh loading systems, and others following a check
- / Also a component of the rail replacement train

Applications

- / Infrastructure with a track gauge of 1,435 mm
- / Track + rail 1/2 renewal measures
- / High-speed lines with short track possessions



STS 1001–STS 1008 Long-Rail Transport Unit

Technical Data

Type	Rns ^{GBX}
Track gauge	1,435 mm

Main dimensions

Length over buffers (LoB)	22.4 meters
Height	corresponds to G1 structure
Width (between the stanchions)	2.71 meters
Number of bogies	2
Number of wheelsets per wagon	4
Wheelbase between bogie pins	16,860 mm
Distance between axles on bogie	1,800 mm
Distance between outer wheelsets (a)	17,660 mm
Height of vehicle floor above TOP	1,250 mm
Loading gauge / structure gauge	G1

Speed

Hauling speed as part of train set	100 km/h
Operating speed	corresponds to loading speed

Weight

Average tare weight	6 x 24 t/wagon = 144 t/unit
Maximum weight per meter	0
Maximum axle load	22.5 t

Brake system

Brake system type	KE-GP-A
Brake blocks	LL – IB 116* Bgu
Braking power percentage	dependent upon loading weight
Transport setting (F/P)	dependent upon operation and network
Handbrake / parking brake fitted	in some cases

On-track operability

Shunting maneuvers not permitted	Hump-shunting, loose shunting and banking not permitted
Sequencing restrictions	head of the train or end vehicle
Smallest traversable curve radius	unloaded 75 meters, loaded 150 meters
Transport in train set	yes

Weather constraints

Ambient temperature (operating mode)	no constraints
--------------------------------------	----------------

Equipment (basic equipment for each machine and features)

Maximum loading capacity	60E1/E2 profile: 42 x 120 m 54E1/E3/E5 profile: 44 x 180 m 49E1/E5 profile: 48 x 120 m 45E2 profile: 48 x 120 m others as per STS Loading
Number of wagons per unit	6
Method of securing load	as per STS Loading Guidelines STS-clamping block
Load bundling	on request
Loading / unloading of the rails (middle of track, on sleeper heads etc.)	as per the Loading System
Performance data	as per the Loading System
Personnel / machine operators / crew (number and qualification)	as per the Loading System
Technical drawing of machines	see TI Wagon Catalogue
Wagon equipment	STS-clamping block, stanchions, bulkhead doors, checker plate steel flooring, STS racks, end vehicle deflector door

STS 2001–STS 2004 Long-Rail Transport Unit

Technical Data

Type	Rs (MAV)
Track gauge	1,435 mm

Main dimensions

Length over buffers (LoB)	19.9 meters
Height	corresponds to G1 structure
Width (between the stanchions)	2.75 meters
Number of bogies	2
Number of wheelsets per wagon	4
Wheelbase between bogie pins	14,860 mm
Distance between axles on bogie	1,800 mm
Distance between outer wheelsets (a)	16,660 mm
Height of vehicle floor above TOP	1,260 mm
Loading gauge / structure gauge	G1

Speed

Hauling speed as part of train set	100 km/h
Operating speed	corresponds to loading speed

Weight

Average tare weight	7 x 22.4 t/wagon = 156.8 t/unit
Maximum weight per meter	4
Maximum axle load	20.0 t

Brake system

Brake system type	KE-GP-A
Brake blocks	LL – IB 116*Bgu
Braking power percentage	dependent upon loading weight
Transport setting (F/P)	dependent upon operation and network
Handbrake / parking brake fitted	in some cases

On-track operability

Shunting maneuvers not permitted	Hump-shunting, loose shunting and banking not permitted
Sequencing restrictions	head of the train or end vehicle
Smallest traversable curve radius	unloaded 75 meters, loaded 150 meters
Transport in train set	yes

Weather constraints

Ambient temperature (operating mode)	no constraints
--------------------------------------	----------------

Equipment (basic equipment for each machine and features)

Maximum loading capacity	60E1/E2 profile: 36 x 120 m 54E1/E3/E5 profile: 40 x 180 m 49E1/E5 profile: 48 x 120 m 45E2 profile: 48 x 120 m others as per STS Loading
Number of wagons per unit	7
Method of securing load	as per STS Loading Guidelines clamping block
Load bundling	on request
Loading / unloading of the rails (middle of track, on sleeper heads etc.)	as per the Loading System
Performance data	as per the Loading System
Personnel / machine operators / crew (number and qualification)	as per the Loading System
Technical drawing of machines	see TI Wagon Catalogue
Wagon equipment	stanchions, bulkhead doors, wooden flooring, STS racks, end vehicle deflector door

STS 3001–STS 3025 Long-Rail Transport Unit

Technical Data

Type	Rs (B)
Track gauge	1,435 mm

Main dimensions

Length over buffers (LoB)	21.7 meters
Height	corresponds to G1 structure
Width (between the stanchions)	2.64 meters
Number of bogies	2
Number of wheelsets per wagon	4
Wheelbase between bogie pins	16,660 mm
Distance between axles on bogie	1,800 mm
Distance between outer wheelsets (a)	18,460 mm
Height of vehicle floor above TOP	1,230 mm
Loading gauge / structure gauge	G1

Speed

Hauling speed as part of train set	100 km/h
Operating speed	corresponds to loading speed

Weight

Average tare weight	6 x 24.4 t/wagon = 146.4 t/unit
Maximum weight per meter	3.7
Maximum axle load	20.0 t

Brake system

Brake system type	KE-GP
Brake blocks	LL – IB 116*Bg
Braking power percentage	dependent upon loading weight
Transport setting (F/P)	dependent upon operation and network
Handbrake / parking brake fitted	no

On-track operability

Shunting maneuvers not permitted	Hump-shunting, loose shunting and banking not permitted
Sequencing restrictions	head of the train or end vehicle
Smallest traversable curve radius	unloaded 75 meters, loaded 150 meters
Transport in train set	yes

Weather constraints

Ambient temperature (operating mode)	no constraints
--------------------------------------	----------------

Equipment (basic equipment for each machine and features)

Maximum loading capacity	60E1/E2 profile: 36 x 120 m 54E1/E3/E4 profile: 40 x 120 m 49E1/E5 profile: 44 x 120 m 45E2 profile: 48 x 120 m others as per STS Loading
Number of wagons per unit	6
Method of securing load	as per STS Loading Guidelines clamping block
Load bundling	on request
Loading / unloading of the rails (middle of track, on sleeper heads etc.)	as per the Loading System
Performance data	as per the Loading System
Personnel / machine operators / crew (number and qualification)	as per the Loading System
Technical drawing of machines	see TI Wagon Catalogue
Wagon equipment	stanchions, bulkhead doors, wooden flooring, STS racks, end vehicle deflector door

Diese Seite in der Version 8/24 nicht sichtbar, da diese STS

Einheit umgebaut wird.

STS 4001 (synthetic sleepers) Long-Rail Transport Unit

Technical Data

Type	Rs (B)
Track gauge	1,435 mm

Main dimensions

Length over buffers (LoB)	21.7 meters
Height	corresponds to G1 structure
Width (between the stanchions)	2.64 meters
Number of bogies	2
Number of wheelsets per wagon	4
Wheelbase between bogie pins	16,660 mm
Distance between axles on bogie	1,800 mm
Distance between outer wheelsets (a)	18,460 mm
Height of vehicle floor above TOP	1,230 mm
Loading gauge / structure gauge	G1

Speed

Hauling speed as part of train set	100 km/h
Operating speed	corresponds to loading speed

Weight

Average tare weight	6 x 24.4 t/wagon = 146.4 t/unit
Maximum weight per meter	0
Maximum axle load	20.0 t

Brake system

Brake system type	KE-GP
Brake blocks	LL – IB 116*Bgu
Braking power percentage	dependent upon loading weight
Transport setting (F/P)	dependent upon operation and network
Handbrake / parking brake fitted	no

On-track operability

Shunting maneuvers not permitted	Hump-shunting, loose shunting and banking not permitted
Sequencing restrictions	head of the train or end vehicle
Smallest traversable curve radius	unloaded 75 meters, loaded 150 meters
Transport in train set	yes

Weather constraints

Ambient temperature (operating mode)	no constraints
--------------------------------------	----------------

Equipment (basic equipment for each machine and features)

Maximum loading capacity	60E1/E2 profile: 36 x 120 m 54E1/E3/E4 profile: 40 x 120 m 49E1/E5 profile: 44 x 120 m 45E2 profile: 48 x 120 m others as per STS Loading
Number of wagons	6
Method of securing load	as per STS Loading Guidelines clamping block
Load bundling	on request
Loading / unloading of the rails (middle of track, on sleeper heads etc.)	as per the Loading System
Performance data	as per the Loading System
Personnel / machine operators / crew (number and qualification)	as per the Loading System
Technical drawing of machines	see TI Wagon Catalogue
Wagon equipment	clamping block, stanchions, bulkhead doors, perforated metal gratings and wooden flooring, STS racks and end-vehicle deflected door

STS 5001–STS 5007 Long-Rail Transport Unit

Technical Data

Type	Rlns
Track gauge	1,435 mm

Main dimensions

Length over buffers (LoB)	21.48 meters
Height	corresponds to G1 structure
Width (between the stanchions)	2.74 meters wagon width, wagon is not equipped with stanchions
Number of bogies	2
Number of wheelsets per wagon	4
Wheelbase between bogie pins	16,150 mm
Distance between axles on bogie	1,800 mm
Distance between outer wheelsets (a)	17,950 mm
Height of vehicle floor above TOP	1,240 mm
Loading gauge / structure gauge	G1

Speed

Hauling speed as part of train set	100 km/h
Operating speed	corresponds to loading speed

Weight

Average tare weight	6 x 27.7 t/wagon = 166.2 t/unit
Maximum weight per meter	0
Maximum axle load	22.5 t

Brake system

Brake system type	Ch-GP-A / KE-GP-A
Brake blocks	LL – IB 116*Bgu
Braking power percentage	dependent upon loading weight
Transport setting (F/P)	dependent upon operation and network
Handbrake / parking brake fitted	no

On-track operability

Shunting maneuvers not permitted	Hump-shunting, loose shunting and banking not permitted
Sequencing restrictions	head of the train or end vehicle
Smallest traversable curve radius	unloaded 75 meters, loaded 150 meters
Transport in train set	yes

Weather constraints

Ambient temperature (operating mode)	no constraints
--------------------------------------	----------------

Equipment (basic equipment for each machine and features)

Maximum loading capacity	60E1/E2 profile: 40 x 120 m 54E1/E3/E4 profile: 44 x 120 m 49E1/E5 profile: 48 x 120 m 45E2 profile: 48 x 120 m others as per STS Loading
Number of wagons per unit	6
Method of securing load	as per STS Loading Guidelines clamping block
Load bundling	on request
Loading / unloading of the rails (middle of track, on sleeper heads etc.)	as per the Loading System
Performance data	as per the Loading System
Personnel / machine operators / crew (number and qualification)	as per the Loading System
Technical drawing of machines	see TI Wagon Catalogue
Wagon equipment	clamping block, stanchions, bulkhead doors, perforated metal gratings and wooden flooring, STS racks and end-vehicle deflected door

Global expertise in
over 100 countries

